



**ROLL TO ROLL  
&  
Flatbed**



## Overview

- > Media Versatility with R-T-R and flatbed operation.
- > Full width belt-driven vacuum flatbed for accurate conveyance of rigid and roll media.
- > Retractable alignment bar for rigid media.
- > A superb fast 50m<sup>2</sup>/hr for quality prints.

## Technical Specification

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>&gt; <b>Print Speed:</b><br/>6 Pass, 55 m<sup>2</sup>/hr<br/><b>Quality:</b> 8 Pass, 40 m<sup>2</sup>/hr<br/><b>High Quality:</b> 12 Pass, 25 m<sup>2</sup>/hr</li> <li>&gt; <b>Number of PrintHeads:</b><br/>8-12 pcs (Polaris Printhead)<br/>2 Printheads per color</li> <li>&gt; <b>Max. Resolution:</b><br/>Up to 1200 x 800 dpi</li> <li>&gt; <b>Media Type:</b><br/>All Kinds of flexible and rigid substrates.</li> </ul> | <ul style="list-style-type: none"> <li>&gt; <b>Max. Media Size:</b><br/>HT3200UV: 3.2m x 50m<br/>HT2500UV: 2.5m x 50m</li> <li>&gt; <b>Max. Media Thickness:</b><br/>5cm</li> <li>&gt; <b>Max. Media Weight:</b><br/>50 Kg/m<sup>2</sup></li> <li>&gt; <b>Ink Type:</b><br/>UV curable</li> <li>&gt; <b>Ink Color:</b><br/>4 to 8 custom colors<br/>C, M, Y, K, LC, LM, LC &amp; White.</li> </ul> |
|---|--|